

Part No.	Size	PATTERN	Diameter	Speed	Load	Tread Depth	Overall Diameter	Overall Width	Max. Load	Max.Press.	TREAD	SIDEWALL	Approved Rim With Range	Long Description	Bullet Points	Sales Description	
																	Range
285-7516AMP/CA2	285/75R16	Pro A/T	16	126/123R	E	12	32.83	11.26	3,750 lbs. / 3,415 lbs	80 psi	2P+2S+1N	2P	7.5-9"	285/75R16 Terrain Pro A/T P 126/123R LR E		729419106911	
305-7016AMP/CA2	305/70R16	Pro A/T	16	124/121R	E	12	32.83	12.24	3,525 lbs. / 3,195 lbs	65 psi	2P+2S+1N	2P	8-9.5"	305/70R16 Terrain Pro A/T P 124/121R LR E		729419106942	
285-7017AMP/CA2	285/70R17	Pro A/T	17	121/118R	E	12	32.76	11.5	3,195 lbs. / 2,910 lbs	80 psi	2P+2S+1N	2P	7.5-9"	285/70R17 Terrain Pro A/T P 121/118R LR E		729419106904	
305-6517AMP/CA2	305/65R17	Pro A/T	17	121/118R	E	12	32.6	12.24	3,195 lbs. / 2,910 lbs	65 psi	2P+2S+1N	2P	8.5-11"	305/65R17 Terrain Pro A/T P 121/118R LR E		729419106935	
315-7017AMP/CA2	315/70R17	Pro A/T	17	121/118R	E	12	34.41	12.72	3,195 lbs. / 2,910 lbs	65 psi	2P+2S+1N	2P	8-11"	315/70R17 Terrain Pro A/T P 121/118R LR E		729419106959	
285-6518AMP/CA2	285/65R18	Pro A/T	18	125/122R	E	12	32.56	11.5	3,640 lbs. / 3,305 lbs	80 psi	2P+2S+1N	2P	8-10"	285/65R18 Terrain Pro A/T P 125/122R LR E		729419106898	
325-6518AMP/CA2	325/65R18	Pro A/T	18	127/124R	E	12	34.61	13.03	3,860 lbs. / 3,525 lbs	65 psi	2P+2S+1N	2P	9-12"	325/65R18 Terrain Pro A/T P 127/124R LR E		729419106973	
275-6020AMP/CA2	275/60R20	Pro A/T	20	123/120S	E	12	32.99	10.98	3,415 lbs. / 3,085 lbs	80 psi	2P+2S+1N	2P	7.5-9.5"	275/60R20 Terrain Pro A/T P 123/120S LR E		729419106874	
285-5520AMP/CA2	285/55R20	Pro A/T	20	122/119S	E	12	32.36	11.69	3,305 lbs. / 3,000 lbs	80 psi	2P+2S+1N	2P	8-10"	285/55R20 Terrain Pro A/T P 122/119S LR E		729419106881	
305-5520AMP/CA2	305/55R20	Pro A/T	20	121/118S	E	12	33.23	12.44	3,195 lbs. / 2,910 lbs	65 psi	2P+2S+1N	2P	8.5-11"	305/55R20 Terrain Pro A/T P 121/118S LR E		729419106928	
325-6020AMP/CA2	325/60R20	Pro A/T	20	126/123S	E	12	35.35	13.03	3,750 lbs. / 3,415 lbs	65 psi	2P+2S+1N	2P	9-12"	325/60R20 Terrain Pro A/T P 126/123S LR E		729419106966	